

UPM Raflatac Technical Information

23-06-2025 EN SI EMEA

Adhesive	RHT
Sales Code	RH0T
Type	Strong permanent
Composition	Hotmelt
Use	Designed specifically for heavy duty applications involving rough surfaces.

Typical technical values

Tack	35	N/25mm	FTM 9
Labelling temperature min	10	°C	
Service temperature min	-20	°C	
Service temperature max	40	°C	

Limitations Due to the aggressive adhesive, the maximum conversion speed is lower than that of standard labelstock. Roll edges usually have an adhesive-free pattern because of the high coat-weight. High temperatures may cause the adhesive to bleed.

Disclaimer The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.